BONA HARD WAX OIL

Bona Hard Wax Oil

Sealing oil

- Plant-based oil/wax blend
- Water and dirt repellent
- Cobalt and ketoxime free

Gloss	
Silkmatt	
Matt.	
X-Matt	
c	

Neu

Bon

2.5L

terd wax oil for wooden floors Hartwachsöl für Holzböden Hule-cim solide bois pour sols en bols Acieta de cera dura para suelos de madera Histwaxolja för trägolv



BONA OIL SYSTEM - UNIQUE CHARACTERS ON WOODEN FLOORS









Bona's complete range of oils are renewable, made using raw vegetable materials and free from hazardous agents such as cobalt and ketoximes (2-butonoxime, butoxime, MEKO) and is very low in odour. Their high oil content ensures a high degree of saturation with fewer applications, for healthy floors and long-lasting protection.

✓ Natural solutions
✓ Child safe

✓ Cobolt free



Bona Hard Wax Oil

Protective indoor oil for wooden floors

Bona Hard Wax Oil delivers long-lasting protection and excellent resistance to wear, scuff marks and moisture. It produces the warm look of an oiled floor, while establishing a hardwearing and stain resistant surface that is spot-repairable and easy to maintain. Bona Hard Wax Oil is highly suitable for floors with underfloor heating. Its leaves an open, breathing surface that reduces the risk of side bonding.

APPLICATION

Bona Hard Wax Oil is suitable for indoor wood floor surfaces. For enhanced protection, apply 2 layers. For colour effects, prepare the surface with Bona Craft Oil and/or Bona Rich Tone, before sealing with 1-2 layers of Bona Hard Wax Oil.

KEY BENEFITS

- Plant-based oil/wax blend
- Extreme water resistance
- Water and dirt repellent
- Fast drying and working process
- Open, breathing surface Inhibits side-bonding
- High coverage rate
- Safe for application on children's toys and countertops, EN 71-3 compliant

TECHNICAL DATA

Product base:	Modified vegetable oils and waxes
Solids content:	Approx. 48%
Sheen (at 60°):	Silkmatt: ≈20, Matt: ≈10, XM: ≈3
Drying time:	Before sanding/recoating: 6-8 hours* Light use: min 16 hours* *under normal indoor conditions, 20°C/60% R.H. ensure proper ventilation.
Application rate:	20-24 m² per litre and layer
Cleaning:	Use clean tools with white spirit and dried material can be removed with white spirit
Safety:	Classified, see safety data sheet for more information
Shelf life:	3 years, from the date of production, in unopened original container
Disposal:	Waste and emptied containers should be handled in accordance with local regulations
Pack sizes:	6 x 1 litre 2 x 2.5 litres 1 x 10 litres

